


# CE RF Exposure Report

**Equipment** : Bluetooth 5.0 BLE Data Module  
**Model No.** : BL654  
**Brand Name** : Laird  
**Applicant** : Laird Technologies  
**Address** : W66N220 Commerce Court, Cedarburg,  
Wisconsin 53012, USA  
**Standard** : EN 62311:2008  
EN 50385:2017  
**Received Date** : Jan. 30, 2018  
**Tested Date** : May 02 ~ May 09, 2018

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

  
James Fan / Assistant Manager

Approved by:

  
Gary Chang / Manager



---

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1	Information.....	4
<b>2</b>	<b>RF EXPOSURE EVALUATION .....</b>	<b>5</b>
2.1	Limits .....	5
2.2	Evaluation Formula for Far-Field.....	6
2.3	Evaluation Results.....	6
<b>3</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>7</b>

---

## Release Record

Report No.	Version	Description	Issued Date
EA813002	Rev. 01	Initial issue	Jun. 25, 2018

# 1 General Description

## 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	V5.0 LE	2402-2480	0-39 [40]	125 kbps
				500 kbps
				1 Mbps
2400-2483.5	V5.0 LE	2402-2480	0-39 [40]	2 Mbps

Note 1: Bluetooth LE (Low energy) uses GFSK modulation.

### 1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Gain (dBi)	Remark
1	Laird	NanoBlue	PCB Dipole	IPEX MHF4	2	Connector Type Antenna
2	Laird	FlexPIFA	PCB Dipole	IPEX MHF4	2	Connector Type Antenna
3	Laird	FlexNotch	PCB Dipole	IPEX MHF4	2	Connector Type Antenna
4	Mag.Layers	EDA-8709-2G4C1-B27-CY	Dipole	IPEX MHF4	2	Connector Type Antenna
5	Laird	mFlexPIFA	PIFA	IPEX MHF4	2	Connector Type Antenna
6	Laird	Laird NFC	NFC	N/A	N/A	Printed PCB Antenna & Connector Type Antenna
7	Laird	BL654-SA PCB printed antenna	Printed PCB	N/A	0	Printed PCB Antenna
8	Walsin	RFDPA870900SBAB8G1	Dipole	SMA	2	Connector Type Antenna

### 1.1.3 EUT Operational Condition

<b>Power Supply Type</b>	1.8Vdc & 3.3Vdc from host
--------------------------	---------------------------

## 2 RF exposure evaluation

### 2.1 Limits

The device shall comply with the relevant limits for general public exposure specified as basic restrictions or reference levels in the Council Recommendation 1999/519/EC as below table.

Reference levels for electric, magnetic and electromagnetic fields  
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	—	$3,2 \times 10^4$	$4 \times 10^4$	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

**Notes:**

1.  $f$  as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any  $68/f^{1.05}$  -minute period ( $f$  in GHz).
4. No E-field value is provided for frequencies  $< 1$  Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.

## 2.2 Evaluation Formula for Far-Field

Follow below formula to evaluate E-field strength.

$$E = \frac{\sqrt{30 * P * G}}{R}$$

Where

P(W) is the input power of antenna

G is the gain of antenna

R(m) Is the distance between the human body and the antenna

## 2.3 Evaluation Results

Frequency Range (MHz)	Maximum E.I.R.P. (dBm)	Distance (m)	Evaluation E-Field Strength (V/m)	Limit (V/m)	PASS / FAIL
2402-2480	9.34	0.2	2.54	61	Pass

### 3 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

#### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin  
Kou District, New Taipei City,  
Taiwan, R.O.C.

#### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,  
Kwei Shan District, Tao Yuan City  
333, Taiwan, R.O.C.

#### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan District, Tao Yuan  
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==